



MIRACHEM INDUSTRIES

B-310, Virwani Industrial Estate
Off Western Express Highway
Goregaon (East), Mumbai - 400 063, India
Tel.: +91 22 42417575 / 29271378
Fax: +91 22 42417550

www.mirachemindustries.com
Email:
admin@mirachemindustries.com
mirachem@bom5.vsnl.net.in
mirachemindustries@gmail.com

SILKY PEACH – 30

Silky Peach – 30 is a specialty-finishing agent for imparting soft handle, providing lubrication and preventing creasing tendency. It is a valuable additive in wash-and-wear finishing for processing Polyester / cotton and polyester/viscose blends.

- Imparts soft handle
- Improvement in tear and abrasion resistance
- Provides lubrication and helps to prevent crease marks on fabric
- Can be used as a self finish or in combination with synthetic resins, like **Miraset – VS**
- Imparts touch of class exuberance and richness to product

Properties:

Appearance	: Colourless liquid
Chemical Nature	: Modified polysiloxane resin
Ionic Nature	: Nonionic
Solubility	: Soluble
pH (2% solution)	: 5.0 ± 1.0
Stability	: Resist to hard water
Compatibility	: Compatible practically with all products used in finishing
Suitability for white goods:	Suitable

Influence on dyed goods

- Shade : Virtually no change
- Fastness properties : Virtually no influence
- Storage Stability : Stable for 3 months if stored in a cool & dry place.
(Not sensitive to frost)

Method of Application:

Silky Peach – 30 is to be diluted in the ratio of 1:4 before use.

Silky Peach – 30 (diluted) may be applied to fabrics.

- Padding:
Silky Peach – 30 → 20 – 40 g/l
- Exhaust:
Silky Peach – 30 → 2 – 3 % (o.w.f)



MIRACHEM INDUSTRIES

B-310, Virwani Industrial Estate
Off Western Express Highway
Goregaon (East), Mumbai - 400 063, India
Tel.: +91 22 42417575 / 29271378
Fax: +91 22 42417550

www.mirachemindustries.com
Email:
admin@mirachemindustries.com
mirachem@bom5.vsnl.net.in
mirachemindustries@gmail.com

For wash – and wear finish by pad-dry-cure method:

Miraset – VS → 60 – 80 g/l (Cross-linking agent with built-in catalyst)

Silky Peach – 30 → 15 – 25 g/l (P. U. based softener)

Mirafin - B → 20 – 30 g/l (A versatile finishing agent suitable for suiting)

General safety instructions

The usual hygiene and safety rules for handling chemicals should be observed in storage, handling and use.
The product should not be swallowed. For further information, please consult existing safety data sheet.

Note :

The data contained in this communication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed. Responsibility for compliance with the requirements of the downstream textile market rests with the textile processor.